

M/V Poprad

European Trading BOXSHAPED River/Sea going with low draft

poprad ship data english ver 09 03 2010

Vessel's name: m/v "Poprad", (ex "Xandrina")

Home Port: Szczecin,

Flag: Polish

Owners: Baltramp Shipping Sp. z o.o.

Built: 1986r., Arminiuswerft GmbH, Bodenwerder - Germany

Type: General cargo, low draft, gearless, sea river, boxed hold, fixed

wheelhouse, collapsable masts

Class: PRS, KM General Cargo Ship I AUT

IMO No.: 8509002

Call Sign: SNBI

GT /NT: 1567 / 659

LOA / Beam: 81,07m / 11,30m

DWAT / draft: Abt. 1980 (class certificate), draft summer 3,72m, draft winter

3,645m, fw allowance 7,5 cm

DWCC Summer: Abt. 1865t with 15 t bunkers and 10t fresh w. and 2,0 t lube oil and

16 t both grain bulkheads, on 3,72m

Winter: Abt. 1803t with 15 t bunkers and 10t fresh w. and 2,0 t lube oil and

16 t both grain bulkheads, on 3,645m

Draft Ballast: Max. ballast (1198mt, less After Peak filled by 80%): abt Fwd dr:

2,97m, Aft dr: 3,17m, with 15 t bunkers and 10t fresh w. and 2,0 t

lube oil and 16 t both grain bulkheads

Min. ballast (347mt, Fore peak and 2 DB P Stb): abt Fwd dr: 1,41m,

Aft dr: 2,41m subject bunkers and FW onboard

Airdraft: See additional info, fore and aft masts lowerable only



Hold: Boxed, double skinned, dimensions without grain bulkheads 51,57 /

 $50,37 \times 9,00 \times 6,08$ m high, steel floored, strengthened for heavy cargo 12,0 mt/sqm, suitable for grab discharge, project or timber cargo: hatch covers hinges located underneath and take 13 cm from

hold height

Hold capacity: Without both grain bulkheads 2797,29 cbm, with both grain

bulkheads: stored both aft: 2702,62 cbm at 49,39 m hold length, stored 1 aft + 1 fwd: 2682,37 cbm at 49,02 m hold length, other

positions see add. info

Hold ventilation: One electrical blower (mushroom) located forecastle deck, 4 pcs vent

outlet flaps located aft hatch coaming

Hatchway: 50,37 m x 9,00m, with the same max clear opening

Hatchway clear open: 49,37m (opened covers)

Hatch covers: Steel, multifold crocodile Kvaerner Hatch Covers, 8 sections (4 aft + 4

fwd), strength 1,09 mt/sqm

Grain bulkheads: 2 grain bulkheads - 5 positions available + 3 parking, both weight 16,0

mt, both volume 38,0 cbm brutto

Grain fitted: Yes, 2 movable grain bulkheads, max wheat intake arr. 1800mt, (sf

arr 40, bulkhead 1 at fr 113, bulkhead 2 at 39, cargo between bulkheads arr 1660mt, and cargo between engine room bulkhead

and grain bulkhead 2 arr 140mt)

Container fitted: No, however, container dovetail sockets welded on hatch covers and

container flush socket for twistlock on tank top, both in 3 rows x 8

bays, TEU intake 72 pcs (48 hold + 24 deck)

River traffic: No aft anchor, river certificate to be renewed

Main Engine: Deutz type SBA 8M 528, 600 kW at 686 revs

Aux. Engine: 1 x Deutz type BA6M 816, 205 kW, at 1800 revs, water cooled

1 x Deutz type F6L 912, 60 kW, at 1800 revs, air cooled 1 x Hatz type 4M 40H, 40 kW, at 1800 revs, air cooled 1 x Deutz type F4L 912, 40 kW, at 1800 revs, air cooled

Bow thruster: Pleuger, 130 kW, electric driven

Speed / consump.: Ballast abt. 10,0 kn, on abt. 3,2 mt Gas Oil, (at wind up to 3B, waves

0,60m (1) as described in Nautical Almanac)), laden abt 9,5kn, on



3,2 mt Gas Oil, (at wind up to 3B, waves 0,60m, (1) as described in

Nautical Almanac))

Port consumption: Abt 0.25 mt G.O. idle

Gasoil capacity: Max 108,4 mt

Lube Oil capacity: Max 5,7 cbm,

Radio Equipm.: GMDSS A1+A2

Other info: Aft rudder Flap type, rescue boat, fresh water 19,3 mt, max ballast

capacity max 1198 cbm

Insurance: H+M: "PZU" (Powszechny Zakład Ubezpieczeń S.A., Poland), H+M

value EUR 600.000,-

P + I: PZU with British Marine terms and reinsurance, Limit USD

50.000.000,-

Next Special Survey: 20 Oct 2013

Next dry docking: 27 Sep 2013

Mobile phone no.: +48 662 03 36 77

Fax no.: +48 606 84 04 72, (within regular GSM range)

Iridium: none

Inmarsat: 426100052@skyfile-c.com.pl